



***Motors for the Long Run!***  
Visit us at [www.marathonelectric.com](http://www.marathonelectric.com)



## Variable Speed SB526 Motor Brochure



"At The Heart Of What Drives Your World"





# Black Max<sup>®</sup> & Blue Max<sup>®</sup> Motors offer MAXimum Features...

## **MAX GUARD<sup>®</sup> Insulation System**

- Is the only insulation system that offers unlimited lead length between the motor and the drive!
- Surpasses the requirements of NEMA MG1, Part 30 and 31
- Is an exclusive patented feature

## **MAXimum Performance**

- Performance matched for operation with any AC drive
- Preferred by leading drive manufacturers

## **MAXimum Flexibility**

- Designed-in flexibility for easy addition of encoders and brakes
- Innovative patented feature called the "fracket" provides option for mounting brakes, encoders, blowers, or combinations of any of the three
- NEMA frame sizes maintained



**MAX GUARD<sup>®</sup> is an exclusive Marathon Electric patented feature!**

**microMAX™  
Inverter Duty**  
1000:1 CT & 20:1 CT



- Designed to replace PMDC, variable, or fixed speed systems.
- 1/8 HP to 10 HP, 1800 RPM, TENV & TEFC, 230 Volt, 230/460 Volt, or 575 Volt.
- TENV rated for 1000:1 Constant torque (0 to base speed).
- TEFC rated for 20:1 Constant torque.
- Cost effective designs available as C-Face, C-Face with rigid base and C-Face with removable rigid base.
- Class H insulation with CR200 corona resistant magnet wire.
- UL, CSA, CE
- No encoder provisions

**Black Max®  
Vector Duty**  
1000:1 CT



- Designed for high performance applications utilizing Closed- or Open-Loop Vector controls or Volts/Hertz drives.
- Stock through 30 HP, 1800 RPM, and 10 HP, 1200 RPM, 230/460 Volt or 575 Volt, TENV.
- Constant torque operation from 0 to base speed on vector drive.
- Lightweight versatile design with encoder and brake provisions included on opposite drive end.
- MAX GUARD® Class F insulation system.
- UL, CSA, CE

**Black Max®  
Explosion Proof**  
1000:1 CT



- Designed for hazardous locations Class I Groups C & D, Class II Groups F & G.
- Stock ratings available from 1/4 HP through 1 HP, 1800 RPM, 230/460 Volt, C-Face with rigid base.
- Constant torque operation from 0 to base speed on vector drive.
- Top mounted (F3) conduit box included (shipped loose).
- MAX GUARD® Class F insulation system.
- Class F normally closed thermostats.
- No encoder provisions

**Blue Max® 2000  
Vector Duty**  
2000:1 CT



- Designed for VFD applications requiring full rated torque at 0 speed using Closed- or Open-Loop (Sensorless) Vector controls.
- 1 HP through 350 HP, 1800 RPM in stock, 230/460 Volt and 460 Volt, C-Face with rigid base (through 100 HP).
- Cast iron frame and brackets for harsh environments and minimal vibration.
- Encoder provisions on all stock ratings.
- Patented "fracket" design provides more options.
- MAX GUARD® Class H insulation system.
- UL, CSA, CE



**Applications...**

- Machine Tools
- Conveyors
- Packaging Equipment
- Batching Machines
- Printing Equipment
- Stair Lifts



**Applications...**

- Material Handling
- Machine Tools
- Conveyors
- Crane and Hoist
- Metal Processing
- Pumps
- Packaging Equipment
- Test Stands



**Applications...**

- Machine Tools
- Conveyors
- Crane and Hoist
- Packaging Equipment

**Applications...**

- Process Lines
- Chemical Plants
- Paper Mills
- Conveyors
- Crane and Hoist



# Blue Max® 2000 Motors For Your Toughest Applications

## Blue Max® 2000 Explosion Proof 2000:1 CT



- Designed for industrial applications in hazardous locations, Class I Groups C & D, Class II Groups F & G, that require precise speed control.
- 1 HP through 20 HP, 1800 RPM, 230/460 Volt, C-Face with rigid base.
- Capability of building ratings up to 150 HP
- Cast iron frame and brackets for dirty, dusty or caustic environments.
- BEI H38 Encoder, 1024 ppr on stock ratings, other encoders available on factory build-ups.
- MAX GUARD® Class F insulation system.

## Blue Max® 2000 Brakemotors 2000:1 CT



- Similar industrial design as the Blue Max® 2000 motor only featured with a brake for temporary slow down and holding.
- Stock ratings from 1 HP through 20 HP, 1800 RPM, 230/460 volt, C-face with rigid base.
- Constant torque operation from 0 to base speed on vector drive.
- Cast iron frame and brackets for dirty, dusty or caustic environments.
- MAX GUARD® Class F insulation system.
- Build-up ratings through 200 HP with brakes up to 1000 lb-ft.

## Blue Max® 2000 Dripproof Force Ventilated 2000:1 CT



- Durable Blue Max® 2000 design, precise speed and torque regulation.
- 30 HP through 1250 HP, factory build-up capabilities.
- Cast iron frame and brackets for industrial durability.
- Constant torque operation from 0 to base speed on vector drive.
- Numerous encoder options and configurations
- MAX GUARD® Class F insulation system.

## Blue Max® 2000 Wide Constant Horsepower 2000:1 CT



- Available in TEBC, TENV, and DPV Blue Max® enclosures.
- Totally Enclosed from 5 HP through 350 HP and Dripproof from 25 HP through 450 HP.
- Up to 4 times base speed, constant horsepower ("field weakening" mode).
- One minute overload @ 150% of rated torque below base speed.
- 125% overload capability to maximum constant HP RPM.
- MAX GUARD® Class F insulation system.
- Class F normally closed thermostats.



### Applications...

- Process Lines
- Chemical Plants
- Paper Mills
- Conveyors
- Crane and Hoist

### Applications...

- Process Lines
- Chemical Plants
- Paper Mills
- Conveyors
- Crane and Hoist



### Applications...

- Center Winders
- Payoff and Tension Reels
- Uncoilers
- Recoilers
- Scrap Choppers
- Slitters

### Applications...

- Center Winders
- Payoff and Tension Reels
- Uncoilers
- Recoilers
- Scrap Choppers
- Slitters



# Best Applications

## Blue Chip® Severe Duty Explosion Proof 2:1 CT to 10:1 CT



- Cast iron construction, 1 HP through 350 HP, UL Listed.
- Class I Groups C & D, Class II Groups F & G, Temperature code T3B.
- Motor nameplate has Variable & Constant torque capability for use with any PWM Drive.
- 1.15 Service factor on sinewave, 1.0 Service factor on VFD power.
- CR<sup>200</sup> corona resistant magnet wire.
- Meets IEEE45 USCG Marine Duty specifications.
- IP54 Construction.

## Blue Chip XRI® Severe Duty & IEEE841 Up to 20:1 CT



- 100% cast iron construction, 3/4 HP through 450 HP.
- Capable of Variable torque and Constant torque.
- 1.15 Service factor on sinewave, 1.0 Service factor on VFD power.
- NEMA Design B provides limited in-rush current when by-passing the VFD.
- Internal and external epoxy coatings.
- MAX GUARD® Class F insulation system.
- Meets IEEE45 USCG Marine Duty Specifications.
- IP54 Construction on XRI Severe Duty and IP56 Construction on IEEE841.

## Washdown PowerWash™ 2:1 CT to 20:1 CT



- USDA-approved white epoxy paint, 1/4 HP through 10 HP.
- 100% stainless steel three phase designs available, 1/2 HP through 10 HP.
- Capable of 10:1 Variable torque and up to 20:1 Constant torque on select ratings.
- 1.15 Service factor on sinewave, 1.0 Service factor on VFD power.
- Internal corrosion resistant coatings on frame, base, endshields, rotor and stator.
- MAX GUARD® Class F insulation system.
- IP55 Construction.

## IEC Globetrotter™ Up to 20:1 CT



- Aluminum construction 63-90 frame, cast iron construction 100-315 frame.
- Capable of 10:1 Variable torque, and up to 20:1 Constant torque on select ratings.
- Meets IEC 34 and IEC 72 standards.
- Design N with NEMA design B torques.
- B3 Mounting (rigid base) in stock; B3/B5 or B3/B14 mountings available.
- MAX GUARD® Class F insulation system.
- IP55 Construction.



### Applications...

- Refineries
- Food Processing
- Mines
- Foundries
- Chemical Plants
- Paper Making
- Marine Duty
- Automotive Plants



### Applications...

- Fans and Blowers
- Pumps
- Compressors
- Machine Tools
- Conveyors



### Applications...

- Machine Tools
- Textile Machinery
- Conveyors
- Pumps
- Blowers

### Applications...

- Dairies
- Beverage Plants
- Food Processing
- Slaughter Houses
- Bakeries
- Pharmaceutical Plants
- Car Washes



# Marathon Electric's "MAX" Family of AC Variable Speed Motors

## Performance and Specification Comparisons



Characteristic	microMAX™	Black Max®	Blue Max®
<b>Electrical Characteristics</b>			
Horsepower range	1/8-10	1/4-30	1-1250
Base speed (# Poles)	4	4 and 6	2, 4, 6, 8, 10, 12
Standard Voltage	230, 230/460, 575	230/460, 575	230/460, 460, 575
Insulation Class	H	F	F (select models are H)
Insulation System	CR200 magnet wire / Class H	MAX GUARD® / Class F	MAX GUARD® / Class F or H
Service Factor (inverter power)	1.0	1.0	1.0
Phase/Base Frequency	3/60	3/60	3/60
Design Code (NEMA)	A	A	A ("B" as noted)
Duty Cycle	Continuous	Continuous	Continuous
Thermal protection	None	Class F thermostats	Class F thermostats
<b>Mechanical Characteristics</b>			
Frame size (mounting)	56-215T	56-286T	143T-6805
Normal NEMA frame size	Yes	Yes	Yes
Enclosure	TENV & TEFC	TENV & EPNV	TENV, TEFC, TEBC, EPNV, DPFV
Frame material	Rolled Steel	Rolled Steel, Aluminum, and Cast Iron	Cast Iron
End bracket material	Aluminum	Aluminum, Cast Iron	Cast Iron
Conduit box material	Steel	Steel	Cast Iron
Fan guard material	Polypropylene	None (all ratings TENV)	Cast Iron
Fan material	Polypropylene	None (all ratings TENV)	Polypropylene
Severe Duty option	No	No	Yes
Lead termination	Terminal block (3 lead TENV) Conduit box (all others)	Conduit box	Conduit box
Standard mounting (stock)	C-Face with Rigid Base and C-Face Round Body	C-Face with Rigid Base	C-Face with Rigid Base (1-100 HP) Rigid base (TEFC and over 100 HP)
Drive end shaft slinger	No	No	Yes
Paint	Black (powder-coat or enamel)	Black (powder-coat or enamel)	Blue (powder-coat or enamel)
Bearings	Ball (C3 fit)	Ball (C3 fit)	Ball (C3 fit); 445T-up Roller
Grease	Mobil POLYREX EM	Mobil POLYREX EM	Mobil POLYREX EM
Standard conduit box assembly position	F3	F1, reversible to F2 (except 56/140 frame steel)	F1, reversible to F2 (F3 available on build-up)
<b>Performance Characteristics</b>			
Constant Torque speed range	20:1 (TEFC), 1000:1 (TENV)	1000:1 (TENV)	2000:1 (all enclosures) TEFC: 20:1 on V/H drives
Constant Horsepower speed range	2:1 (90-120 Hz intermittent)	2:1 (90-120 Hz intermittent)	1.5:1-4:1
Temperature rise	B	F	F (TENV & TEFC) B (TEBC)
Encoder provisions (stock motors)	No	Yes	Yes
High Breakdown Torque	Yes	Yes	Yes
<b>Other Characteristics</b>			
Agency listings	UL Recognized, CSA Certified, CE	UL Recognized, CSA Certified, CE	UL Recognized, CSA Certified, CE
Warranty	3 years	3 years	3 years



Marathon Electric Manufacturing Corporation  
A REGAL-BELOIT COMPANY

P.O. Box 8003 ▪ Wausau, WI 54402

Phone: (715) 675-3311

Fax: (715) 675-8030

Website: [www.marathonelectric.com](http://www.marathonelectric.com)



SB526-5750M/5M-2/07/TP/SK